

Contents

1	FIGURE 6 – BACCALA ET AL. (2016) DTF: UNIFIED ASYMPTOTIC THEORY	1
	Generating data set for analysis	1
	Equation	2
	Connectivity diagram	2
	DTF estimation	4
	PDC estimation	5
	$ PDC(\lambda) ^2$ Matrix Layout Plotting	6
	Figure depicted in the article Baccala et al (2016)	7
	Some remarks:	7

1 FIGURE 6 – BACCALA ET AL. (2016) DTF: UNIFIED ASYMPTOTIC THEORY

DESCRIPTION:

Routine **figure6_example2_ipdc_idtf_ns2000.m** publish

Linear trivariate VAR(2) model

LA Baccala, DY Takahashi, K Sameshima (2016) Directed Transfer Function: Unified Asymptotic Theory and Some of its Implications. *IEEE Transactions on Biomedical Engineering* **PP**.

<http://dx.doi.org/10.1109/TBME.2016.2550199>

Example 2: Trivariate loop VAR(2) model $x_1 \implies x_2 \implies x_3 \overset{\text{---}}{\wedge}$

Contents

- Generating data set for analysis
- Equation
- Connectivity diagram
- DTF estimation
- PDC estimation
- $|PDC(\lambda)|^2$ Matrix Layout Plotting
- Figure depicted in the article Baccala et al (2016)
- Some remarks:

Generating data set for analysis

```
clear; clc; format compact
flgPlotStyle = 'Print'; % or 'Screen' mode
flgRandomize = 0; % Generate the specific data set used in Fig. 1.
ns = 2000; % number of sample points
nDiscard = 20000; % number of points discarded at beginning of simulation
p = 2; % model order

if (exist('figure6_example2_ipdc_idtf_ns2000.mat') == 2) & is_octave & ~
    flgRandomize,
    load figure6_example2_ipdc_idtf_ns2000
else
    [u] = fbaccala2016_example2( ns, nDiscard, flgRandomize );
    if ~is_octave & ~flgRandomize,
        save figure6_example2_ipdc_idtf_ns2000 u
    end;
```

```
end;

chLabels = []; % Using default labeling schema for channel identification
```

```
=====
"DTF Unified Asymptotic Theory" Example 2
x1 ==> x2 ==> x3
^-----/
=====
```

Equation


$$\begin{aligned}
 x_1(n) &= 0.95\sqrt{2}x_1(n-1) - 0.9025x_1(n-2) \\
 &\quad + 0.35x_3(n-1) + w_1(n) \\
 x_2(n) &= 0.5x_1(n-1) + 0.5x_2(n-1) + w_2(n) \\
 x_3(n) &= x_2(n-1) - 0.5x_3(n-1) + w_3(n)
 \end{aligned}$$

Equation (9) from Baccala et al. *IEEE Trans Biomed Engin.*, 2016.

with with the innovations covariance matrix given by

$$\Sigma_w = \begin{bmatrix} 1 & 5 & 0.3 \\ 5 & 100 & 2 \\ 0.3 & 2 & 1 \end{bmatrix}$$

Connectivity diagram



Example 2 loop connectivity structure following (9) and (10). Signals from any structure reach all other structures. from Baccala et al. *IEEE Trans Biomed Engin.*, 2016.

Data pre-processing: detrending and normalization options

```
flgDetrend = 1; % Detrending the data set
flgStandardize = 0; % No standardization
[nChannels, nSegLength] = size(u);
if nChannels > nSegLength, u = u.';
```

```

[nChannels,nSegLength] = size(u);
end;
if flgDetrend,
    for i=1:nChannels, u(i,:) = detrend(u(i,:)); end;
    disp('Time series were detrended.');
```

```

end;
if flgStandardize,
    for i=1:nChannels, u(i,:) = u(i,:)/std(u(i,:)); end;
    disp('Time series were scale-standardized.');
```

MVAR model estimation

```

maxIP = 30;           % maximum model order to consider.
alg = 1;              % 1: Nutall-Strand MVAR estimation algorithm
criterion = 1;        % 1: AIC, Akaike Information Criteria
disp('Running MVAR estimation and GCT analysis routines.')
```

```

[IP,pf,A,pb,B,ef,eb,vaic,Vaicv] = mvar(u,maxIP,alg,criterion);
```

```

disp(['Number of channels = ' int2str(nChannels) ' with ' ...
    int2str(nSegLength) ' data points; MAR model order = ' int2str(IP) '.']);
```

```

Running MVAR estimation and GCT analysis routines.
```

```

maxOrder limited to 30
```

```

IP=1   vaic=60428.213072
```

```

IP=2   vaic=54036.613963
```

```

IP=3   vaic=54039.508093
```

```

Number of channels = 3 with 2000 data points; MAR model order = 2.
```

Testing for adequacy of MAR model fitting through Portmanteau test

```

h = 20; % testing lag
MVARadequacy_signif = 0.05; % VAR model estimation adequacy significance
    % level
aValueMVAR = 1 - MVARadequacy_signif; % Confidence value for the testing
flgPrintResults = 1;
```

Granger causality test (GCT) and instantaneous GCT

```

gct_signif = 0.01; % Granger causality test significance level
igct_signif = 0.01; % Instantaneous GCT significance level
flgPrintResults = 1;
[Tr_gct, pValue_gct, Tr_igct, pValue_igct] = gct_alg(u,A,pf,gct_signif, ...
    igct_signif,flgPrintResults);
```

```

-----
GRANGER CAUSALITY TEST
=====
Connectivity matrix:
      NaN      0      1.00
    1.00      NaN      0
      0      1.00      NaN
Granger causality test p-values:
      NaN      0.56      0
```

```

      0      NaN      0.71
    0.55      0      NaN
-----
              INSTANTANEOUS GRANGER CAUSALITY TEST
=====
Instantaneous connectivity matrix:
      NaN      1.00      1.00
    1.00      NaN      1.00
    1.00      1.00      NaN
Instantaneous Granger causality test p-values:
      NaN      0      0
      0      NaN      0
      0      0      NaN
>>>> There are 3 pairs of channels with
      significant Instantaneous Causality.

```

DTF estimation

DTF analysis results are saved in **c** structure. See `asympt_dtf.m` or issue `>> help asympt_dtf` command for more detail.

```

metric = 'info'; % euc = original PDC or DTF;
           % diag = generalized PDC (gPDC) or directed coherence (DC);
           % info = information PDC (iPDC) or iDTF.

nFreqs = 128;
alpha = 0.01;

c = asympt_dtf(u,A,pf,nFreqs,metric,alpha);

```

```

* Information DTF and asymptotic statistics

```

$|DTF(\lambda)|^2$ Matrix Layout Plotting

```

switch lower(flagPlotStyle)
case 'print'
    flgColor = [0]; % white background
    flgMax = 'TCI';
    flgSignifColor = 1; % black + gray
    flgScale = 2; % [0 max(flagMax)]
otherwise % 'screen'
    flgColor = [1]; % Colored background
    flgMax = 'TCI';
    flgSignifColor = 3; % red + green
    flgScale = 2; % [0 1]/[0 .1]/[0 .01]
end;

% -----Plotting options flag setting-----
% [1 2 3 4 5 6 7]
flagPrinting=[1 1 1 2 2 0 0];
% | | | | | 7 Spectra(0: w/o SS; 1: Linear; 2: log-scale)
% | | | | | 6 Coherence
% | | | | 5 Plot lower confidence limit (legacy)
% | | | 4 Plot upper confidence limit
% | | 3 Significant DTF(w) in red line (legacy)
% | 2 Patnaik threshold level in black dashed-line

```

```

%           1 plot DTF
%-----


fs = 1;           % sampling frequency

w = fs*(0:(nFreqs-1))/2/nFreqs;
w_max = fs/2;

h = figure;
set(h,'NumberTitle','off','MenuBar','none', ...
    'Name','[Asymptotic DTF] Fig 6. Example 2 - Trivariate loop iDTF, ns = 2000'
    )
[hxlabel hylabel] = xplot(c,...
    flgPrinting,fs,w_max,chLabels,flgColor,flgScale,flgMax,flgSignifColor);
%xplot_title(alpha,metric, measure(c));

[ax,hT] = suplabel(['Example 2 - Trivariate Loop: sigma2 = 100; ns = ' ...
    int2str(ns) ' data points; p = ' int2str(p) ' \alpha = ' ...
    int2str(100*alpha) '%.'], 't');
set(hT,'FontSize',10); % Subtitle font size

```



Uncomment the command line bellow to generate an eps output file

```
% print -depsc2 -painters Fig6_example2_dtf_ns2000.eps
```

PDC estimation

PDC analysis results are saved in **d** structure. See `asympt_dtf.m` or issue `>> help asympt_pdc` command for more detail.

```

nFreqs = 128;
metric = 'info'; % euc = Euclidian = original PDC;
%           % diag = diagonal = generalized PDC or gPDC;
%           % info = information = iPDC

```

```

alpha = 0.01;

d = asymp_pdc(u,A,pf,nFreqs,metric,alpha);

% Power spectra and coherence calculation
d.SS = ss_alg(A, pf, nFreqs);
d.coh = coh_alg(d.SS);

if alpha ~= 0,
    % Statistically significant PDC on frequency scale
    pdc_temp = ((abs(d.pdc)-d.th) > 0).*d.pdc + ((abs(d.pdc)-d.th) <= 0)*(-1);
    pdc_temp(ind2sub(size(pdc_temp),find(pdc_temp == -1))) = NaN;
    d.pdc_th = pdc_temp;
end;

```

```

* Information PDC and asymptotic statistics

```

$|PDC(\lambda)|^2$ Matrix Layout Plotting

```

% -----Plotting options flag setting-----
%           [1 2 3 4 5 6 7]
flgPrinting=[1 1 1 2 2 0 0];
%           | | | | | 7 Spectra(0: w/o SS; 1: Linear; 2: log-scale)
%           | | | | | 6 Coherence
%           | | | | 5 Plot lower confidence limit (legacy)
%           | | | 4 Plot upper confidence limit
%           | | 3 Significant DTF(w) in red line (legacy)
%           | 2 Patnaik threshold level in black dashed-line
%           1 plot DTF
% -----
fs = 1;           % sampling frequency
w_max = fs/2; % x-axis maximum value
h = figure;
set(h,'NumberTitle','off','MenuBar','none', ...
    'Name','[Asymptotic DTF] Fig 6. Example 2 - Trivariate loop iPDC, ns = 2000'
    )
[hxlabel hylabel] = xplot(d,...
    flgPrinting,fs,w_max,chLabels,flgColor,flgScale,flgMax,flgSignifColor);

%xplot_title(alpha,metric, measure(c));

[ax,hT]=suplabel(['Example 2 - Trivariate Loop: sigma2 = 100; ns = ' ...
    int2str(ns) ' data points; p = ' int2str(p) ' \alpha = ' ...
    int2str(100*alpha) '%.'],'t');
set(hT,'FontSize',10); % Subtitle font size

```


Uncomment the command line bellow to generate an eps output file

```
print -depsc2 -painters Fig6_example2_ipdc_ns2000.eps
```

Figure depicted in the article Baccala et al (2016)

Figure 6, reproduced from article.


Example 2 - Trivariate Loop: $\sigma_3^2 = 100$; ns = 2000 data points; $p = 2$ $\alpha = 1\%$.



Some remarks:

1. As usual, figure 6 underwent some cosmetic edit

This completes the **Figure 6** generation (Baccala et al, 2016)'

a**b**